Naval Research Laboratory – Space Sciences Division – Washington, D.C.

DCN-0018

GLAST ENGINEERING CHANGE ORDER	Drawing No. GLT-LLR-00-10	Current Rev. G3	Outstanding ECO NONE	ECO No. 1

Drawing Title : **Close-Out Plate Y**

[X] Class 1 [ ] Class 2 Sheet 1 of 1

WBS No. :

Reason : **Threaded holes must be plugged prior to application of plating.**

Next Assy. : **GLT-LLR-00-00**

Used On : **GLAST**

Submitted By : **Paul Dizon** Date : **7 January 2004**

Effective : Serial : ALL
Date : 7 JAN 2004
Other :

Type of EO : [X] Advance notice of change; drawing will be revised
[ ] Deviation; drawing will not be revised
[ ] Other (EXPLAIN) :

Disposition	Use as is	RWK	Scrap	See Above
Raw Material				
Parts in Process	X			
Assemblies				

Other :

Description :

1. MODIFY NOTE 3 AS SHOWN:

3 Electroless nickel plating applied in accordance with SAE AMS-C-26074, Class 4, Grade A (not to exceed .0013 inch). All threaded holes must be plugged prior to plating. All dimensions after plating.

2. ADD NOTE FLAG AS SHOWN:

a. Zone P-11

3



Drafter Date

Checker Date

Engineer PVDizon 1-7-04 Date

Stress Date

QA 1/13/04 Date

Proj Mgr 1-13-04 Date

Manuf. Date

Date

Issued By : Date

INC. REV.

GLAST ENGINEERING CHANGE ORDER	Drawing No.	Current Rev.	Outstanding ECO	ECO No.
	GLT-LLR-00-10	G3	NONE	1

Description :

b. Zones H-6 through H-10



Drafter
Date

Checker
Date

Engineer
1-7-04
Date

Stress
Date

QA
1/13/04
Date

Proj Mgr
1-13-04
Date

Manuf.
Date

Issued By :
Date

INC. REV.

Naval Research Laboratory – Space Sciences Division – Washington, D.C.

DCN-0019

GLAST ENGINEERING CHANGE ORDER	Drawing No. GLT-LLR-00-10	Current Rev. G3	Outstanding ECO NONE	ECO No. 2

Drawing Title : **Close-Out Plate Y**

[X] Class 1 [ ] Class 2 Sheet 1 of 3

WBS No. :

Reason : **Redefine Datum C to a feature which defines a clearer definition for the centerline of the part**

Next Assy. : **GLT-LLR-00-00**

Used On : **GLAST**

Submitted By : **Paul Dizon** Date : **7 January 2004**

Effective : Serial : ALL

Date : 7 Jan 2004

Other :

Type of EO :
[X] Advance notice of change; drawing will be revised
[ ] Deviation; drawing will not be revised
[ ] Other (EXPLAIN) :

Disposition	Use as is	RWK	Scrap	See Above
Raw Material				
Parts in Process	X			
Assemblies				

Other :

Drafter Date

Checker Date

Engineer Date

Stress Date

QA 1-13-04 Date

Proj Mgr 1-13-04 Date

Manuf. Date

Date

Issued By : Date

INC. REV.

Description :

1. Was Condition (Section C-C, in Zone L-2):



1. Now Condition (Section C-C, in Zone L-2) – Change Positional Tolerance to Profile Tolerance:



Naval Research Laboratory – Space Sciences Division – Washington, D.C.

DCN-0019

GLAST ENGINEERING CHANGE ORDER	Drawing No.	Current Rev.	Outstanding ECO	ECO No.
	GLT-LLR-00-10	G3	NONE	2

Description :

2. Was Condition (Section B-B, in Zone L-2):



2. Now Condition (Section B-B, in Zone L-2) – Change Positional Tolerance to Profile Tolerance:



Drafter	Date
Checker	Date
Engineer	1-9-04 Date
Stress	Date
QA	1-13-04 Date
Proj Mgr	1-13-04 Date
Manuf.	Date
Issued By :	Date
INC. REV.	

Naval Research Laboratory – Space Sciences Division – Washington, D.C.

DCN-0019

GLAST ENGINEERING CHANGE ORDER	Drawing No.	Current Rev.	Outstanding ECO	ECO No.
	GLT-LLR-00-10	G3	NONE	2

Description :

3. Was Condition (Zone D-8 and E-6):



3. Now Condition (Zone D-8 and E-6):



Drafter	Date
Checker	Date
Engineer	Date
Stress	Date
QA	1-13-04 Date
Proj Mgr	1-13-04 Date
Manuf.	Date
Issued By :	Date
INC. REV.	

LAT-DS-00921-08	APPROVAL	DATE
CAL PROJECT MANAGER	WCR	15 JAN 04
CAL LEAD ENGINEER	PVD	14 JAN 04
CAL QA	JWL	15 JAN 04

MASTER DOCUMENT
GLAST-CAL CM FILE COPY



RELEASED FOR MANUFACTURE
15 JAN 2004

NOTE 1:
Main dimension inches, dimension within brackets are metric equivalent

NOTE 2:
All helicoils per SAE Aerospace Standard MA3279
installed in accordance to SAE Aerospace Standard MA1567
Clean helicoils with isopropyl alcohol prior to installation
Install insert 0.75-1.5 pitch below surface. Remove tang.

NOTE 3:
Electroless nickel plating applied in accordance with SAE AMS-C-26074, Class 4, Grade A (not to exceed .0013 inch). All threaded holes must be plugged prior to plating. All dimensions after plating.

NOTE 4:
Marking: Drawing number and serial number shall be engraved on the parts using normal gordon style characters, number size 7 (1/8 inch) as specified LAT-DS-00921/YY with YY serial number 01, 02 to 36.

NOTE 5:
All dimensions and tolerances are defined with part fastened on a flat plate using the eleven ∅3 holes with ⌴5 countersunk and the ten ∅10.5 holes.

NOTE 6:
Break all corners and sharp edges to R 0.015" max.

Part Number	Thread size/pitch (mm)	Length (mm)	Description	Quantity
MA 3279-201	MJ2.5 x 0.45	5	Insert, Helical Coil, Free Running, CRES	16
MA 3279-151	MJ2.5 x 0.45	3.75	Insert, Helical Coil, Free running, CRES	31

Dimensions: inch (mm)
Unless specified:
Tolerances: ± 0.004
Surface finish: Ra 0.06

A0
Scale: 1:1

Material: 7075 T7351
Surface treatment: Electroless Nickel (note 3)
Quantity: 40

Drawing: Edy mai 2003
Checked: Ferreira
Approuved: -

Laboratoire Leprince-Ringuet
ECOLE POLYTECHNIQUE
91128 PALAISEAU
TEL: 01 69 33 31 87
FAX: 01 69 33 39 62

CLOSE OUT PLATE Y

GLT-LLR-00-10

Fichier: GLT-LLR-00-10 H (Closeout plate Y).CATDrawing